



## TMA Table-Medal-Automat

Proof-Quality meets >> Fast-Forward-Technology

**TMA 350**

|                                                        |                                               |                                                        |
|--------------------------------------------------------|-----------------------------------------------|--------------------------------------------------------|
| <b>Technical data</b>                                  | Press force                                   | 3.500 kN                                               |
|                                                        | Coin or medal size                            | Ø10 - ø60* mm                                          |
|                                                        | Max. stroke                                   | 120 mm                                                 |
|                                                        | Number of strokes (Manual mode)               | ≤ 9 /min                                               |
|                                                        | Number of strokes (Automatic mode)            | ≤ 15 /min**                                            |
|                                                        | Ejector force                                 | 100 kN                                                 |
|                                                        | Ejector stroke                                | 32 mm                                                  |
| <b>Dimensions</b>                                      | Tool installation space (W x D)               | 400 x 360 mm                                           |
|                                                        | Tool installation height                      | 550 mm                                                 |
|                                                        | Floor space requirements (W x D x H)          | 2,2 x 2,8 x 2,7 m                                      |
|                                                        | Weight (without oil)                          | 8.600 kg                                               |
| <b>Speed</b>                                           | Closing                                       | 200 mm/s                                               |
|                                                        | Pressing                                      | 4,1 mm/s                                               |
|                                                        | Opening                                       | 160 mm/s                                               |
| <b>Supply</b>                                          | Max. power consumption                        | 22 kW                                                  |
|                                                        | Compressed air supply                         | min. 6 bar                                             |
|                                                        | Oil quantity                                  | 130 l                                                  |
| <b>Miscellaneous</b>                                   | Different kinds of feeding solutions          | round / shaped / bimetal / bars                        |
|                                                        | Highest productivity                          | manual / semi-automatic / automatic                    |
|                                                        | Multiple pressing with adjustable press force | •                                                      |
|                                                        | Hologram pressing                             | •                                                      |
|                                                        | Dwell time                                    | •                                                      |
|                                                        | Tool cleaning                                 | •                                                      |
|                                                        | LCD-Touch-Panel                               | •                                                      |
|                                                        | Optoelectronic 2-hand control switch          | •                                                      |
|                                                        | Servo drive with Blue Competence Lable®       | •                                                      |
|                                                        | Ergonomic design minimum floor space          | •                                                      |
|                                                        | Quality control section                       | •                                                      |
|                                                        | Precision Medal Tool                          | •                                                      |
| Refrigerant air dryer for clean and dry compressed air | •                                             |                                                        |
| <b>Options</b>                                         | Camera inspection system                      |                                                        |
|                                                        | Several options for loading                   | Magazine tubes / Bimetal / Magazine trays for ≤ ø18 mm |

\*in silver and gold, depending on blank thickness

\*\*in silver and gold, guide value coin size ø38,5mm

