



OKP Downstroking Press

Compact design with high flexibility

OKP

Technical data	Press force	3.150 – 25.000 kN
	Blank	≤ 150*mm
	Max. stroke	120 - 300 mm
	Number of strokes	≤ 12 /min**
	Ejector force	100 - 600 kN
	Ejector stroke	30 - 50 mm
Dimensions	Tool installation space (W x D)	405 x 520mm – 940 x 1100 mm
	Tool installation height	600 -1000 mm
	Floor space requirement (W x D x H)	5 x 1,8 x 2,9m – 5 x 3,6 x 4,9 m
	Weight (without oil)	9.500 – 52.100 kg
Speed	Closing	175 - 250 mm/s
	Pressing	2,2 – 10,4 mm/s
	Opening	175 - 250 mm/s
Supply	Max. supply consumption	27,5 - 125 kW
	Compressed air supply	≥ 6 bar
Miscellaneous	Multiple pressing	•
	Adjustable dwell time	•
	Adjustable closing stroke and pressing speed	•
	LCD-Touch-Operator panel	•
	Separate 2-Hand operator panel	•
	USB-port for data exchange	•
	Noise protection cabinet	•
Safety devices acc. CE	•	
Options	Teleservice	•
	Tool	•

* depending on material and press size

** depending on manual or automatic operation

